

| Art. No. | Höhe | Gewinde | Schlüsselweite | Bemessungsspannung | | Prüfwechselfspannung | Biegefestigkeit | Zugfestigkeit | Torsionsfestigkeit | Min. Anzugsdrehmoment | Max. Anzugsdrehmoment |
|----------|--------|---------|----------------|--------------------|---------|----------------------|---------------------|-------------------------|-----------------------|------------------------|------------------------|
| Part No. | Height | Thread | Wrench Size | Rated Voltage | | Test voltage | Flexural Resistance | Resistance of Extension | Resistance of Torsion | Min. tightening Torque | Max. tightening Torque |
| | | | | [kV] AC | [kV] DC | [kV] AC | [kN] | [kN] | [Nm] | [Nm] | [Nm] |
| 05779 | 20 | M6 | 17 | 0,6 | 0,8 | 3 | 1 | 2 | 10 | 2,7 | 3 |
| 05780 | 30 | M6 | 30 | 1,5 | 0,8 | 10 | 3 | 6 | 20 | 11 | 12 |
| 05781 | 35 | M6 | 32 | 1,5 | 1,8 | 12 | 4,5 | 8 | 20 | 11 | 12 |
| 05782 | 35 | M8 | 32 | 1,5 | 1,8 | 12 | 5 | 8 | 50 | 18 | 20 |
| 05783 | 40 | M8 | 40 | 2 | 2,4 | 15 | 6 | 11 | 50 | 18 | 20 |
| 05784 | 40 | M10 | 40 | 2 | 2,4 | 15 | 6 | 10 | 75 | 36 | 40 |
| 05786 | 45 | M8 | 46 | 2 | 2,4 | 15 | 6 | 8 | 50 | 18 | 20 |
| 05787 | 45 | M10 | 46 | 2 | 2,4 | 15 | 8 | 10 | 90 | 36 | 40 |
| 05788 | 50 | M10 | 36 | 2 | 2,4 | 15 | 4,5 | 9 | 75 | 36 | 40 |
| 05789 | 60 | M10 | 40 | 3 | 3,6 | 20 | 4,5 | 20 | 90 | 18 | 20 |
| 05790 | 50 | M8 | 36 | 2 | 2,4 | 15 | 4,5 | 9 | 50 | 18 | 20 |
| 05791 | 40 | M12 | 40 | 2 | 2,4 | 15 | 7,5 | 11 | 90 | 36 | 40 |
| 05792 | 30 | M8 | 30 | 1,5 | 1,8 | 10 | 3 | 7 | 40 | 18 | 20 |
| 05793 | 25 | M5 | 22 | 1 | 1,2 | 6 | 1 | 3 | 10 | 2,3 | 2,5 |
| 05794 | 50 | M6 | 36 | 2 | 2,4 | 15 | 4 | 9 | 20 | 11 | 12 |
| 05800 | 30 | M6 | 30 | 1,5 | 1,8 | 10 | 4 | 6 | 15 | 11 | 12 |
| 05801 | 35 | M6 | 32 | 1,5 | 1,8 | 12 | 4 | 8 | 15 | 11 | 12 |
| 05802 | 35 | M8 | 32 | 1,5 | 1,8 | 12 | 5 | 8 | 35 | 18 | 20 |

Version 1.0 21.06.2022