



Article	Descriptions	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U3	U4	V
23011	160 A 4P	122	158	150	99	124	69	44	90	130	7 (M6x16)	30	130	175	24	15	9	6.5	3	79	150	153	189	37.5
23021	160 A 3P+N	122	158	150	99	124	69	44	90	130	7 (M6x16)	30	130	175	24	15	9	6.5	3	79	150	153	189	37.5
23012	160 A 4P with clamps	122	158	150	99	124	69	44	90	130	7 (M6x16)	30	130	175	22.5	14	9	6.5	3	79	150	153	189	37.5
23022	160 A 3P+N with clamps	122	158	150	99	124	69	44	90	130	7 (M6x16)	30	130	175	22.5	14	9	6.5	3	79	150	153	189	37.5
23013	250 A 4P	135	205	150	122	124	78	48	109	170	7 (M6x16)	45	182	230	28.5	25	12.5	11	3	102.5	150	121	189	45
23023	250 A 3P+N	135	205	150	122	124	78	48	109	170	7 (M6x16)	45	182	230	28.5	25	12.5	11	3	102.5	150	121	189	45
23014	400 A 4P	147	205	150	122	124	78	48	109	170	7 (M6x16)	45	182	230	28.5	25	12.5	11	3	102.5	150	121	189	45
23024	400 A 3P+N	147	205	150	122	124	78	48	109	170	7 (M6x16)	45	182	230	28.5	25	12.5	11	3	102.5	150	121	189	45
23015	630 A 4P	193	293	210	162	175	108	72	144	240	7 (M6x16)	65	260	301	31.5	30	15.5	11	6	146	250	213	256	65
23025	630 A 3P+N	193	293	210	162	175	108	72	144	240	7 (M6x16)	65	260	301	31.5	30	15.5	11	6	146	250	213	256	65
23016	1000 A 4P	204	293	210	162	175	108	72	144	240	7 (M6x16)	65	260	301	36.5	35	16.5	14	6	146	250	213	256	65
23026	1000 A 3P+N	204	293	210	162	175	108	72	144	240	7 (M6x16)	65	260	301	36.5	35	16.5	14	6	146	250	213	256	65
23017	1250 A 4P	290	385	241	245	206	127	84	225	170	9 (M8x20)	85	344	490	50	50	25	18	10	192.5	330	244	287	95
23027	1250 A 3P+N	290	385	241	245	206	127	84	225	170	9 (M8x20)	85	344	490	50	50	25	18	10	192.5	330	244	287	95

U3) Minimum distance with the external door coupling installed directly on the switch shaft.

U4) Minimum distance with the external door coupling installed on a extension shaft.