



Article	Description	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U3	U4	V
23001	160 A	122	158	150	99	124	69	44	90	130	7 (M6x16)	30	130	175	24	15	9	6.5	3	79	150	153	189	37.5
23002	160 A with clamps	122	158	150	99	124	69	44	90	130	7 (M6x16)	30	130	175	22.5	14	9	6.5	3	79	150	153	189	37.5
23003	250 A	135	205	150	122	124	78	48	109	170	7 (M6x16)	45	182	230	28.5	25	12.5	11	3	102.5	150	153	189	45
23004	400 A	147	205	150	122	124	78	48	109	170	7 (M6x16)	45	182	230	28.5	25	12.5	11	3	102.5	150	153	189	45
23005	630 A	193	293	210	162	175	108	72	144	240	7 (M6x16)	65	260	301	31.5	30	15.5	11	6	146	250	213	256	65
23006	1000 A	204	293	210	162	175	108	72	144	240	7 (M6x16)	65	260	301	36.5	35	16.5	14	6	146	250	213	256	65
23007	1250 A	290	385	241	245	206	127	84	225	170	9 (M8x20)	85	344	490	50	50	25	18	10	192.5	330	244	287	95

U3) Minimum distance with the external door coupling installed directly on the switch shaft.
 U4) Minimum distance with the external door coupling installed on a extension shaft.