



Article	Description	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	U3	U4	V	X	Y
23101	160 A	145	161	224	105	92	141	37,5	7	246	140	191	145	122	38	30	30	18	15	24	9	6,5	153	189	3	79	150
23103	250 A	170	208	236	124	109	170	45	7	350	189	202	163	137	44	45	45	25	20	22,5	10	9	153	189	3	102,5	150
23104	400 A	180	208	236	124	109	170	45	7	350	189	202	163	137	44	45	45	25	25	28,5	12,5	11	153	189	3	102,5	150
23105	630 A	244	297	337	164	149	265	65	7	423	269	277	230	194	56	65	65	35	30	31,5	15,5	11	213	256	6	146	250
23106	1000 A	255	297	337	164	149	265	65	7	423	269	277	230	194	56	65	65	35	35	36,5	16,5	14	213	256	6	146	250
23107	1250 A	370	389	378	244	225	347	95	9	618	351	315	271	228	70	85	85	60	50	50	25	18	244	287	10	192,5	330
23108	1600 A	485	389	378	244	225	347	95	9	756	351	315	271	228	70	85	85	100	50	85	40	14	244	287	10	192,5	330

U3) Minimum distance with the external door coupling installed directly on the switch shaft.

U4) Minimum distance with the external door coupling installed on a extension shaft.